



**INSTRUMENT
APPROACH
CHART - ICAO****AERODROME ELEV 28 FT**
HEIGHTS RELATED TO
THR RWY 25C - ELEV 22 FTTOWER 118.2
APPROACH 119.1
DIRECTOR 119.5**HONG KONG / INTL (VHHH)
ILS RWY 25C
CAT II & III****Warnings**

1. LOC ITFC UNUSABLE BEYOND 19° RIGHT OF COURSE
2. PILOTS SHOULD MONITOR FOR FALSE CAPTURE OF LOC AND GP BY COMPARING INDICATIONS WITH AIRCRAFT POSITION AND ALTITUDE

Notes

1. DME is required.
2. If unable RNP (e.g. Loss of GNSS), revert to RNAV 1 (DME/DME/IRU) and inform ATC. Continue on the procedure tracks. Request ATC assistance as required. Critical DME: TD required.
3. Simultaneous dependent operation is authorized with RWY 25L.

**MISSED APPROACH**

Climb initially to 4 000 ft and track 254°M to HH821, then turn right to HH822. Proceed to VH523 and cross VH523 between 3 000 ft and 4 000 ft. From VH523, climb to 5 000 ft and track to VH526 and GONAT.
Speed restriction: 185 KIAS maximum until VH523, then maintain 230 KIAS until VH526, then maintain 210 KIAS until GONAT.

DME ITFC	13.6	13	12	11	10	9	8	7	6	5	4	3	2	1
DIST THR (NM)	13.4	12.8	11.8	10.8	9.8	8.8	7.8	6.8	5.8	4.8	3.8	2.8	1.8	0.8
ALTITUDE (FT)	4500	4290	3950	3610	3280	2940	2610	2280	1950	1620	1290	970	650	330
Missed Approach Climb Gradient		OCA (OCH)												
		A	B	C	D									
ILS CAT I	2.5%	500 (478)				Ground Speed	kt	80	100	120	140	160	180	
	4.0%	222 (200)												
ILS CAT II	4.0%	122 (100)				HH832-THR (13.4 NM)	min:s	10:03	8:02	6:42	5:44	5:01	4:28	
VISUAL CIRCLING NOT AVAILABLE		N / A				ROD (5.2%)	ft / min	420	530	640	740	850	960	

CHANGE: Editorial & Reversion Procedure.

ILS RWY 25C APPROACH**NAVIGATION AIDS**

Navaid/Ident	Frequency	Coordinates		Remarks
Localizer/ITFC	109.3 MHz	22 18 30.88N	113 53 26.53E	Course 254°M
Glide Path	332.0 MHz	22 19 13.45N	113 55 24.77E	3° glide slope Co-located
DME/ITFC	CH 30X			

TABULAR DESCRIPTION: ILS RWY 25C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (KIAS)	VPA	Navigation Specification
01	IF	RIVMI	-	-	+3.0	-	-	-6000 +4500	-	-	RNP 1/ RNAV 1
02	TF	CANUP	-	284 (281)	+3.0	5.1	-	+4500	@180	-	RNP 1/ RNAV 1
01	IF	GONAT	-	-	+3.0	-	-	@5000	@210	-	RNP 1/ RNAV 1
02	TF	HH827	-	161 (158)	+3.0	4.2	-	+4500	-	-	RNP 1/ RNAV 1
03	TF	CANUP	-	224 (221)	+3.0	4.8	-	+4500	@180	-	RNP 1/ RNAV 1
01	IF	CANUP	-	-	+3.0	-	-	+4500	@180	-	Conventional
02	-	HH832	-	254 (251)	+3.0	4.4	-	-	@180	-	Conventional
03	-	RW25C	Y	254 (251)	+3.0	13.4	-	-	-	-	Conventional
04	CF	HH821	-	254 (251)	+3.0	-	-	-	-185	-	RNP 1/ RNAV 1
05	TF	HH822	-	340 (337)	+3.0	4.4	-	-	@185	-	RNP 1/ RNAV 1
06	TF	VH523	-	062 (059)	+3.0	4.6	-	-4000 +3000	@185	-	RNP 1/ RNAV 1
07	TF	VH526	-	071 (068)	+3.0	14.5	-	-	@230	-	RNP 1/ RNAV 1
08	TF	GONAT	-	071 (068)	+3.0	7.0	-	@5000	@210	-	RNP 1/ RNAV 1

Note: Coding is not provided for final approach segment. Please refer to the chart for altitude and speed restrictions.

WAYPOINT LIST

ILS RWY 25C		
Waypoint Identifier	Coordinates (WGS-84)	
RIVMI (IAF)	22 24 03.96N	114 19 09.28E
GONAT (IAF)	22 32 32.30N	114 15 27.06E
HH827	22 28 39.55N	114 17 09.59E
CANUP (IF)	22 25 02.54N	114 13 46.40E
HH832 (FAP)	22 23 36.12N	114 09 16.39E
RW25C (THR)	22 19 12.85N	113 55 36.78E
HH821	22 17 54.88N	113 51 34.92E
HH822	22 21 58.90N	113 49 43.76E
VH523	22 24 20.51N	113 53 58.89E
VH526	22 29 52.41N	114 08 27.15E
ITFC DME 18.0 NM		
ITFC DME 13.6 NM		
ITFC DME 0.2 NM		