

**HONG KONG / INTL (VHHH)
RNP Z RWY 25C
(LNAV/VNAV only)**

TRANSITION ALTITUDE 9000

TCH 50 AT DISPLACED THR

113°50'E 114°00'E 114°10'E 114°20'E

HH821 (MAPt) RW25C

HH835 (FAF) 4 500

CANUP (IF) 4 500

FROM RIVMI or GONAT

VPA 2.9° (5.07%) 254'

2 900

THR ELEV 22

14.4 17.8 NM FROM MAPt

Missed Approach Climb Gradient		OCA (OCH)											
		A	B	C	D								
LNAV/VNAV	2.5%	500 (478)				Ground Speed	kt	80	100	120	140	160	180
VISUAL CIRCLING NOT AVAILABLE		N / A				HH835-THR (14.4 NM)	min:s	10:47	8:38	7:11	6:10	5:24	4:48
						ROD (5.1%)	ft / min	410	510	620	720	820	920

Amendment 1/25

RNP Z RWY 25C APPROACH**TABULAR DESCRIPTION: RNP Z RWY 25C**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (KIAS)	VPA	Navigation Specification
01	IF	RIVMI	-	-	+3.0	-	-	-6000 +4500	-	-	RNP APCH
02	TF	CANUP	-	284 (281)	+3.0	5.1	-	+4500	@180	-	RNP APCH
01	IF	GONAT	-	-	+3.0	-	-	@5000	@210	-	RNP APCH
02	TF	HH827	-	161 (158)	+3.0	4.2	-	+4500	-	-	RNP APCH
03	TF	CANUP	-	224 (221)	+3.0	4.8	-	+4500	@180	-	RNP APCH
01	IF	CANUP	-	-	+3.0	-	-	+4500	@180	-	RNP APCH
02	TF	HH835	-	254 (251)	+3.0	3.4	-	@4500	@180	-	RNP APCH
03	TF	RW25C	Y	254 (251)	+3.0	14.4	-	@72	-	-2.9	RNP APCH
04	CF	HH821	-	254 (251)	+3.0	-	-	-	-185	-	RNP APCH
05	TF	HH822	-	340 (337)	+3.0	4.4	-	-	@185	-	RNP APCH
06	TF	VH523	-	062 (059)	+3.0	4.6	-	-4000 +3000	@185	-	RNP APCH
07	TF	VH526	-	071 (068)	+3.0	14.5	-	-	@230	-	RNP APCH
08	TF	GONAT	-	071 (068)	+3.0	7.0	-	@5000	@210	-	RNP APCH

WAYPOINT LIST

RNP Z RWY 25C		
Waypoint Identifier	Coordinates (WGS-84)	
RIVMI (IAF)	22 24 03.96N	114 19 09.28E
GONAT (IAF)	22 32 32.30N	114 15 27.06E
HH827	22 28 39.55N	114 17 09.59E
CANUP (IF)	22 25 02.54N	114 13 46.40E
HH835 (FAF)	22 23 55.53N	114 10 16.99E
RW25C (THR)	22 19 12.85N	113 55 36.78E
HH821	22 17 54.88N	113 51 34.92E
HH822	22 21 58.90N	113 49 43.76E
VH523	22 24 20.51N	113 53 58.89E
VH526	22 29 52.41N	114 08 27.15E